

Product data sheet

Specifications



Sensor, SpaceLogic SLP Series, air quality, CO2, temperature, room, BACnet MSTP/Modbus, matte white housing

SLPSXCX

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	SpaceLogic
Product or Component Type	Sensor
product name	SpaceLogic Room Unit
Type of Measurement	Carbon Dioxide (CO2) Temperature
Device Application	HVAC Temperature control Fan speed controller
Product certifications	CE conforming to EN 61000-6-2 CE conforming to EN 61000-6-3 CE conforming to EN 61326-1 RCM EAC ICES-003 CULus
Communication Port Protocol	BACnet Modbus
Display Type	Without Display
Location	Living Space
Mounting Support	Wall Mount
Depth	0.9 in (24 mm)
Height	3.3 in (85 mm)
Width	4.5 in (115 mm)
Network Frequency	50 Hz 60 Hz
Ambient air temperature for operation	32...122 °F (0...50 °C)
Standards	UL 916 FCC Part 15 class B
Color	White
Sensor Type	Transmitter NDIR (non-dispersive infrared)
[Us] Rated Supply Voltage	24 V AC 20...30 V DC
Device presentation	Complete product
Surface Finish	Matte

Complementary

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	ABS (acrylonitrile butadiene-styrene)
Function Available	With temperature sensor With CO2 sensor
Repeat accuracy	+/- 20 ppm
Connections - terminals	Screw terminal - 2 AWG 24...AWG 18)
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers

Environment

Temperature setting range	50...95 °F (10...35 °C) 32...122 °F (0...50 °C)
---------------------------	--

Ordering and shipping details

Category	US1BMS180230
Discount Schedule	BMS1
GTIN	3606481900890
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.59 in (14.2 cm)
Package 1 Width	3.86 in (9.8 cm)
Package 1 Length	1.89 in (4.8 cm)
Package 1 Weight	6.3 oz (180 g)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	89bfcc78-dfb0-469a-8211-c50fc133952d
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.