

Product data sheet

Specifications



network interface module, Modicon STB, standard, Ethernet, modbus TCP/IP, 10-100Mbits

STBNIP2311

 To be discontinued on: Dec 1, 2027

 To be end-of-service on: Dec 31, 2035

 To be discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon STB distributed I/O solution
Product or Component Type	Standard Network Interface Module

Complementary

Integrated connection type	Ethernet Modbus TCP/IP IEEE 802.3 2 female RJ45 double shielded twisted pair via Ethernet network) Ethernet Modbus TCP/IP IEEE 802.3 HE-13 RS232 port) Ethernet Modbus TCP/IP IEEE 802.3 8-way female RS232 port)
Number of segments	1 primary, maximum 6 extensions
Structure type	Industrial LAN
Number of addressable I/O module	0...32 per island
Input current	550 mA supply circuit
Nominal output current	0.575 A 140...158 °F (60...70 °C) 1.2 A
Output voltage	5.25 V DC +/- 0.21 %)logic bus
Exchange mode	Half or full duplex
Transmission Rate	10/100 Mbit/s
Communication Service	SNMP agent BootP/DHCP protocol Modbus TCP/IP messaging Embedded web (configuration,diagnostics and access to variable)
Power supply type	SELV
Local signalling	1 LED ACT 1 LED island state (RUN) 1 LED module error (ERR) 1 LED MS 1 LED NS 1 LED power supply (PWR) 1 LED test mode (TEST)
Height	1.6 in (40.5 mm)
Width	5.1 in (130 mm)
Depth	2.8 in (70 mm)
Product Weight	0.320 lb(US) (0.145 kg)

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

IP Degree of Protection	IP20
Marking	CE
Product certifications	UL ODVA C-tick ATEX Cat 3G CSA
Ambient air temperature for operation	32...140 °F (0...60 °C) without derating -13...158 °F (-25...70 °C) with derating factor
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % 140 °F (60 °C) without condensation
Operating altitude	<= 6561.68 ft (2000 m)
Vibration resistance	3 gn 58...150 Hz) on 35 mm DIN rail 5 gn 58...150 Hz) on 35 mm DIN rail +/-0.35 mm 10...58 Hz)
Shock resistance	30 gn 11 msIEC 88 reference 2-27

Ordering and shipping details

Category	US1PC3218215
Discount Schedule	PC32
GTIN	3595864062273
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.693 in (4.300 cm)
Package 1 Width	2.874 in (7.300 cm)
Package 1 Length	5.118 in (13.000 cm)
Package weight(Lbs)	6.032 oz (171.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	12.015 lb(US) (5.450 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	F760fd97-89c1-4651-a374-9b8eff254b6a
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No

Dimensions Drawings

Dimensions

