Product data sheet

Specifications

Plantroom Controller, SpaceLogic MP-C-36A, BACnet/IP, 36pts: 8 UI/Os (Uc), 8 Relay Outs, 20 UI/Os (Ub)

SXWMPC36A10001

Product availability: Stock - Normally stocked in distribution facility

Main

Maximum Number of I/O Expansion Module	3
Topology	Star Daisy chain Rapid Spanning Tree Protocol (RSTP)
Width	9.2 in (234 mm)
Mounting Mode	DIN Rail Mount Panel-mounted
Product Certifications	RCM CE cUL Listed UL Listed
Power Consumption in W	18 W
Power Consumption in VA	33 VA
Clock Drift	+/- 1 min/month
Device Application	Low voltage rooftop Air flow control
Product or Component Type	Field Controller
Device short name	MP-C-36A
Function Available	Programmable Smart Sensor Input
Model	MP-C-36A
Network Frequency	50 Hz 60 Hz
Ambient Air Temperature for Storage	-40…158 °F (-40…70 °C)
IP Degree of Protection	IP20
Input/Output Type	20 universal I/O 8 universal I/O
Input Voltage	-0.5...24 V DC for universal input
Memory Type	123 kB backup 32 MB flash 128 MB RAM
Communication Port Support	ETHERNET 10/100BASE-TX
[Us] Rated Supply Voltage	24 V AC +/- 20 % 24...30 V DC 21...33 V DC
Number of Outputs	8 form A relay output

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	2.5 in (64 mm)
Protection Type	MOV suppression Internal fuse
Output Voltage	250 V AC,2 A for form A relay output 30 V DC,2 A for form A relay output -0.5...24 V DC for universal output
Number of Port	2 RJ45 1 USB type A female 1 USB device port Mini-B

Complementary

Backup time	7 days
Flame retardance	UL94-5V
Communication port protocol	BACnet IP
Standards	UL 916 ICES-003 EN 61000-6-2 EN 50491-5-3 EN 60730-1 EN 60730-2-11 EN 50491-3 EN 61000-6-3 EN 50491-5-2 FCC part 15 Subpart B class B
Range compatibility	SpaceLogic IP controller

Ordering and shipping details

Category	US1BMS180230
Discount Schedule	BMS1
GTIN	3606481355485
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	4.88 in (12.4 cm)
Package 1 Length	2.83 in (7.2 cm)
Package 1 Weight	21.9 oz (620 g)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	636
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	5f015d09-43c1-4be7-9233-b3e007760745
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.