

Product data sheet

Specifications



universal automation Wifi Interface - IP20 - with RJ45 and micro USB connectors

TCSEGWB131W

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Accessory / separate part category	Communication accessory
Accessory / Separate Part Type	Wireless access point
Accessory / separate part destination	Smart phone Phablet Variable speed drive PC Tablet PLC
Operating Distance	50...150 m

Complementary

Range Compatibility	Altivar Machine ATV320 Altivar Machine ATV340 Altivar Process ATV600 Altivar Process ATV900 Altivar Process Modular Modicon M251 Modicon M580 Altivar Soft Starter ATS480
Kit composition	Battery USB cable Ethernet cable Quick start guide
Function Available	Automatic detection
Connector type	Female RJ45 automatic negotiation of 10/100 Mbit/s Micro USB type A female
Communication Port Protocol	DHCP PPPoE (Point-to-Point Protocol over Ethernet) Ethernet TCP/IP ICMP
Method of access	CSMA/CA
Operating System	Windows 7 Mac iOS Android Windows XP Windows 8 Windows Vista Windows 10
System Requirements	Google Chrome Microsoft internet explorer Apple Safari Firefox
Supply	Rechargeable internal battery
Local signalling	LEDs (green/red) for Ethernet port activity 1 LED (blue/orange) for Wi-Fi ON 1 LED (green/red) for battery status 1 LED (green) for power supply

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Weight	0.562 lb(US) (0.255 kg)
----------------	-------------------------

Environment

IP Degree of Protection	IP20
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	32...104 °F (0...40 °C)
Standards	IEEE 802.11g IEEE 802.11n IEEE 802.3 IEEE 802.3u IEEE 802.11b
Product Certifications	FCC CE IC

Ordering and shipping details

Category	US1CP4B22149
Discount Schedule	CP4B
GTIN	3606481907004
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.874 in (7.300 cm)
Package 1 Width	3.858 in (9.800 cm)
Package 1 Length	5.866 in (14.900 cm)
Package weight(Lbs)	9.065 oz (257.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	15.274 lb(US) (6.928 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	288
Package 3 Height	41.339 in (105.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	198.716 lb(US) (90.136 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No