

Product data sheet

Specifications



ConneXium Extended Managed Switch - 8 ports for copper - Coated

TCSESM083F23F1C

Product availability : Non-Stock - Not normally stocked in distribution facility

Main

Range of product	ConneXium
Product or Component Type	Ethernet TCP/IP managed switch
Product Specific Application	For severe environments
Concept	Transparent Ready
Communication Port Protocol	Ethernet TCP/IP SSH HTTP HTTPS SNMP RS232 LLDP Telnet SNTP MRP (Media Redundancy Protocol)
Port Ethernet	10/100BASE-TX - 8 copper cable
Maximum number of switches in cascade	Unlimited
Cybersecurity	Port hardening

Complementary

Integrated connection type	Shielded RJ45 copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E copper cable
Maximum cable distance between devices	328.08 ft (100 m) copper cable
Ethernet service	Configuration via web server VLAN Multicast filtering Data stream control IGMP Snooping SNMP-Traps and SYSLOG
Communication Service	TFTP Quality of Service (QoS) Port monitoring Port mirroring Address conflict detection
Diagnostics run time	Signal contact Self test
Maximum number of switches in a ring	50
Redundancy	HiPER ring RSTP Redundant network coupling

[Us] rated supply voltage	24...48 V
Supply voltage limits	18...60 V DC SELV
Power Consumption in W	10 W
Electrical connection	2 removable connectors 2 ways power supply
Mounting Support	35 mm symmetrical DIN rail
Marking	CE UL RCM ATEX
Function Available	Alarms (Traps) System information Report Trap log
Local signalling	for P1 P2 power supplies 1 dual colour LED (green/yellow) for fault 1 LED (red) for ring manager 1 dual colour LED (green/yellow) for stand-by 1 LED (red) for signal contact 1 1 LED (yellow) for signal contact 2 1 LED (yellow) for channel diagnostic 1 LED per channel (green/yellow) Device status
Alarm output	2 voltfree contact 2 A
Alarm function	Power supply fault Data link status High temperature External memory removed
Ethernet cabling system	TF switches
Width	4.72 in (120 mm)
Height	5.39 in (137 mm)
Depth	4.53 in (115 mm)
Net Weight	2.20 lb(US) (1 kg)

Environment

Ambient air temperature for operation	-40...185 °F (-40...85 °C)
Relative Humidity	10...95 % non-condensing
IP degree of protection	IP30
Protective treatment	Conformal coating
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Standards	UL 508 EN/IEC 61131 IEC 61850-3 CSA C22.2 No 213 Class I Division 2 UL 1604 Class 1 Division 2
Product certifications	CE UL RCM ATEX LR GL BV

Ordering and shipping details

Category	18481 - CONNEXIUM NETWORKING HARDWARE
Discount Schedule	PC40
GTIN	3595864115467
Nbr. of units in pkg.	1
Package weight(Lbs)	4.13 lb(US) (1.873 kg)

Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	8.27 in (21 cm)
Package 1 width	8.66 in (22 cm)
Package 1 Length	9.06 in (23 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	1
Package 2 Weight	5.20 lb(US) (2.358 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Unit Type of Package 3	S04
Number of Units in Package 3	2
Package 3 Weight	8.57 lb(US) (3.887 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	15.75 in (40 cm)
Package 3 Length	23.62 in (60 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

