

Product data sheet

Specifications



daisy chaining Bus X cable kit,
Modicon X80, for racks, 2
connectors SUB-D9, 28m

TSXCBY280KT

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range of Product	Modicon Premium Automation platform
Accessory / separate part category	Connection accessories
Accessory / Separate Part Type	Connection kit
Accessory / separate part designation	Daisy chaining Bus X cable kit
Accessory / separate part destination	For multitracks configuration

Complementary

Cable length	91.9 ft (28 m)
Electrical connection	2 connectors SUB-D 9
Kit composition	1 cable + 2 transient voltage suppressors
Product Weight	6.75 lb(US) (3.06 kg)

Ordering and shipping details

Category	US1PC2222558
Discount Schedule	PC22
GTIN	3595864104041
Returnability	No
Country of origin	TN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.543 in (9.000 cm)
Package 1 Width	14.961 in (38.000 cm)
Package 1 Length	19.685 in (50.000 cm)
Package weight(Lbs)	7.926 lb(US) (3.595 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	25.422 lb(US) (11.531 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	39 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	29 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	57
Circularity Profile	No need of specific recycling operations
Take-back	No