

Product data sheet

Specifications



OneMotorCable extension SH3 motor to Lexium 62 drive, 1,5MM2, M23, UL, 15m

VW3EF143R150

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	PacDrive 3
Product or Component Type	Hybrid cable

Complementary

Range Compatibility	Lexium 62
Product compatibility	LXM 62 servo drive SH3070 servo motor SH3100 servo motor
Type of Cable	Shielded cable
Connector type	2 x M23 quicklock, round shape
Material	Metal
Accessory / separate part destination	Holding brake Hiperface DSL shielded
Cable length	49.2 ft (15 m)
Product Weight	7.275 lb(US) (3.300 kg)
Accessory / separate part category	Connection accessories

Ordering and shipping details

Category	US1PC5218353
Discount Schedule	PC52
GTIN	3606489926144
Returnability	No
Country of origin	PL

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.1 in (5.4 cm)
Package 1 Width	15.7 in (40.0 cm)
Package 1 Length	15.7 in (40.0 cm)
Package weight(Lbs)	7.3 lb(US) (3.3 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	26 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	19 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	21
Circularity Profile	End of Life Information
Take-back	No