

Product data sheet

Specifications



pre-assembled cable kit - 6 I/O, 1 STO insert for motion sequence - 5 m

VW3L2M211R50

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Pre-assembled cable kits for motion sequence with 2 I/O, 1 STO insert
Accessory / Separate Part Type	Cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives with printed circuit board connectors
Cable length	16.4 ft (5 m)
Additional information	With integrated cable entry with strain relief With insert equipped with 2 I/O and 1 safe torque off via M8 connector

Complementary

Range Compatibility	Lexium ILA Lexium ILE Lexium ILS
Communication interface	I/O for motion sequence
Electrical connection	Printed circuit board connector drive Cable end open
Product Weight	2.2 lb(US) (1 kg)

Ordering and shipping details

Category	US1PC5618289
Discount Schedule	PC56
GTIN	3389118367418
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.2 in (3.0 cm)
Package 1 Width	11.8 in (30.0 cm)
Package 1 Length	11.8 in (30.0 cm)
Package weight(Lbs)	2.98 lb(US) (1.35 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	163 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	155 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No