

Product data sheet

Specifications



cable for creating control cord sets,
Lexium, 3 x (2 x 0.14mm²) + (2 x
0.34mm²), 100m

VW3M8222R1000

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range of Product	Lexium
Accessory / separate part category	Connection accessories
Accessory / Separate Part Type	Encoder cable
Product or Component Type	Connecting cable
Device Application	For creating control cordsets for SinCos Hiperface encoders
Accessory / separate part destination	From servo motor to servo drive
Cable composition	3 x (2 x 0.14 mm ²) + (2 x 0.34 mm ²)

Complementary

Range Compatibility	Lexium 32 Altivar Process ATV900 Altivar Machine ATV340
Cable length	328.08 ft (100 m)
Product Weight	12.3 lb(US) (5.6 kg)

Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51
GTIN	3606480166716
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.1 in (13.0 cm)
Package 1 Width	16.5 in (42.0 cm)
Package 1 Length	16.5 in (42.0 cm)
Package weight(Lbs)	13.788 lb(US) (6.254 kg)
Unit Type of Package 2	S06
Number of Units in Package 2	8
Package 2 Height	28.9 in (73.5 cm)
Package 2 Width	23.6 in (60.0 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	31.5 in (80.0 cm)
Package 2 Weight	138.962 lb(US) (63.032 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	73 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	35 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.8 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	32 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No