Product data sheet

Specifications

Cable, Lexium 32i, preassembled for STO safety function, 3 m, M8

VW3M9403

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Lexium 32i
Product or Component Type	Cable
Accessory / separate part category	Connection accessory
Product compatibility	Connector module VW3M91 safe torque off safety function Connector module VW3M92 safe torque off safety function

Complementary

Cable length	9.8 ft (3 m)
Electrical connection	M8 female connector, 1 free end, 1
Cable composition	3 x 0.34 mm²
Standards	IEC 61800-5-2
wire colour	White STO_A Brown STO_B Green STO_COM
Product Weight	0.262 lb(US) (0.119 kg)

Ordering and shipping details

Category	US1PC5618289
Discount Schedule	PC56
GTIN	3606480595578
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.8 in (2 cm)
Package 1 Width	5.9 in (15 cm)
Package 1 Length	6.3 in (16 cm)
Package weight(Lbs)	4.2 oz (119 g)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	11.8 in (30 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	15.7 in (40 cm)
Package 2 Length	23.6 in (60 cm)
Package 2 Weight	4.348 lb(US) (1.972 kg)
Unit Type of Package 3	S03
Number of Units in Package 3	18
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	6.294 lb(US) (2.855 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Environmental footprint

Total lifecycle Carbon footprint	**0.1 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**93**
Circularity Profile	**End of Life Information**
Take-back	**No**