

Product data sheet

Specifications



Cable, Lexium 32i, preassembled for STO safety function, 10 m, M8

VW3M9410

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Lexium 32i
Product or Component Type	Cable
Accessory / separate part category	Connection accessory
Product compatibility	Connector module VW3M91 safe torque off safety function Connector module VW3M92 safe torque off safety function

Complementary

Cable length	32.8 ft (10 m)
Electrical connection	M8 female connector, 1 free end, 1
Cable composition	3 x 0.34 mm²
Standards	IEC 61800-5-2
wire colour	White STO_A Brown STO_B Green STO_COM
Product Weight	0.774 lb(US) (0.351 kg)

Ordering and shipping details

Category	US1PC5618289
Discount Schedule	PC56
GTIN	3606480595592
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.984 in (2.500 cm)
Package 1 Width	11.693 in (29.700 cm)
Package 1 Length	14.449 in (36.700 cm)
Package weight(Lbs)	12.981 oz (368.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	11.811 in (30.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	10.858 lb(US) (4.925 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	93
Circularity Profile	End of Life Information
Take-back	No