

Product data sheet

Specifications



cable for pulse/direction signal,
Lexium SD3, 5V, shielded, 0.5m

VW3S8201R05

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / Separate Part Type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and external impulsion generator
Range Compatibility	Lexium SD3
Type of Cable	Shielded cable
Cable length	1.6 ft (0.5 m)

Complementary

Product Compatibility	SD326
[Uc] control circuit voltage	5 V
Electrical connection	1 connector 24-pole Molex SD326) Cable end open external impulsion generator)

Ordering and shipping details

Category	US1PC5518286
Discount Schedule	PC55
GTIN	3389119224567
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.787 in (2.000 cm)
Package 1 Width	7.874 in (20.000 cm)
Package 1 Length	11.024 in (28.000 cm)
Package weight(Lbs)	2.116 oz (60.000 g)
Unit Type of Package 2	S04
Number of Units in Package 2	60
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	9.370 lb(US) (4.250 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	240
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	55.116 lb(US) (25.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No