


Product data sheet

Specifications



Wear part, fan for variable speed drive, Altivar Process 600 900, IP55, up to 22kW, from 380 to 480V

VX5VP50A001

Product availability: Stock - Normally stocked in distribution facility

Main

Range Compatibility	Altivar Process 600/900
Accessory / Separate Part Type	Internal fan
Accessory / separate part category	Cooling accessory
Product or Component Type	Fan

Complementary

Kit composition	Fan Mounting bracket Instruction sheet
-----------------	--

Product compatibility	Variable speed drive ATV650 wall mount 0.75 kW 380...480 V Variable speed drive ATV650 wall mount 1.5 kW 380...480 V Variable speed drive ATV650 wall mount 2.2 kW 380...480 V Variable speed drive ATV650 wall mount 3 kW 380...480 V Variable speed drive ATV650 wall mount 4 kW 380...480 V Variable speed drive ATV650 wall mount 5.5 kW 380...480 V Variable speed drive ATV650 wall mount 7.5 kW 380...480 V Variable speed drive ATV650 wall mount 11 kW 380...480 V Variable speed drive ATV650 wall mount 15 kW 380...480 V Variable speed drive ATV650 wall mount 18.5 kW 380...480 V Variable speed drive ATV650 wall mount 22 kW 380...480 V Variable speed drive ATV950 wall mount 0.75 kW 380...480 V Variable speed drive ATV950 wall mount 1.5 kW 380...480 V Variable speed drive ATV950 wall mount 2.2 kW 380...480 V Variable speed drive ATV950 wall mount 3 kW 380...480 V Variable speed drive ATV950 wall mount 4 kW 380...480 V Variable speed drive ATV950 wall mount 5.5 kW 380...480 V Variable speed drive ATV950 wall mount 7.5 kW 380...480 V Variable speed drive ATV950 wall mount 11 kW 380...480 V Variable speed drive ATV950 wall mount 15 kW 380...480 V Variable speed drive ATV950 wall mount 18.5 kW 380...480 V Variable speed drive ATV950 wall mount 22 kW 380...480 V
-----------------------	--

Ordering and shipping details

Category	US1CP4E22276
Discount Schedule	CP4E
GTIN	3606480716331
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.795 in (7.100 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	6.772 in (17.200 cm)
Package 1 Length	9.291 in (23.600 cm)
Package weight(Lbs)	9.347 oz (265.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	5.071 lb(US) (2.300 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No