

45° Liquidtight Connectors with Insulated Throat - Malleable Iron Hot Dip Galvanized

Features

- Hot dip galvanized
- Liquidtight, raintight, oiltight
- Suitable for wet locations
- Tapered threaded male hub NPT
- Insulated throat protects conductors from abrasion damage
- Compact slim diameter with small turning radius



Applications

- To secure, ground and seal liquidtight conduit to a box or enclosure
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-1




Standard Material

- Malleable iron
- Steel locknut

Standard Finish

- Hot dip galvanized



UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div. 2, Class II Div. 1 and 2, Class III Div. 1 and 2 are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-1

Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches		
						A	B	C
231HDG	03735	1/2"	10	100	25	1.36	1.50	2.51
232HDG	03736	3/4"	10	100	35	1.61	1.73	2.70
233HDG	03737	1"	5	50	26	1.89	2.11	3.05
234HDG	03740	1-1/4"	2	20	19	2.39	2.56	3.65
235HDG	03738	1-1/2"	2	20	23	2.62	2.77	4.01
236HDG	03739	2"	2	20	34	3.24	3.38	4.64