

Flexible Liquidtight Conduit

Metallic - Reel

Features

- Crush and corrosion resistant steel core for lasting mechanical protection
- Durable PVC jacket is oil, heat and sunlight resistant (UV)
- Smooth interior for easy wire pull through
- 3/8" thru 1-1/4" with continuous bonding strip

Applications

- Suitable for damp or wet locations in commercial and industrial applications.
- Suitable as a grounding conductor when used for circuits rated up to 20A for 3/8" & 1/2" trade sizes and 60A for 3/4" through 1-1/4" trade sizes in lengths six feet or less per NEC Article 250.118(6). Larger sizes require separate grounding conductor.
- Listed for direct burial and in poured concrete
- Class I Div. 2: Article 501.10 (B)(2) & 501.30 (B)
- Class II Div. 1: Article 502.10 (A)(2) & 502.30 (B) Div. 2: 502.10 (B)(2)
- Class III Div. 1: Article 503.10 (A)(3) & 503.30 (B) Div. 2: 503.10 (B)

Standard Material

- PVC jacket
- Galvanized Steel Core



Catalog Number	UPC	Size	Feet Reel	Ship Case	Weight/ Case	Inside Diameter		Outside Diameter		Outside Diameter PVC Jacket	
						Min.	Max.	Min.	Max.	Min.	Max.
6100RUL	03823	3/8"	1000'	1000'	272	.484	.504	.594	.614	.69	.71
6101RUL	03824	1/2"	1000'	1000'	312	.622	.642	.732	.765	.82	.84
6101RUL500	03966	1/2"	500'	500'	156	.622	.642	.732	.765	.82	.84
6102RUL	03825	3/4"	500'	500'	229	.82	.84	.93	.96	1.03	1.05
6103RUL	03826	1"	200'	200'	127	1.04	1.066	1.201	1.226	1.29	1.315
6104RUL	03827	1-1/4"	200'	200'	155	1.38	1.41	1.54	1.57	1.63	1.66
6105RUL	03828	1-1/2"	100'	100'	130	1.575	1.60	1.735	1.77	1.865	1.90
6106RUL	03829	2"	100'	100'	154	2.02	2.045	2.18	2.215	2.34	2.375