

15S3HNV

Low voltage transformer, non ventilated dry type, 3 phase, 15kVA, 240x480V primary, 120/240V secondary, Type 3R



Main

Product	Non-Ventilated Transformer
Enclosure Code	17E
Insulation Temperature	428.0000000000 °F (220 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	15 kVA
Secondary Voltage	120/240 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	150 °C
Winding Material	Aluminium

Ordering and shipping details

Category	US10PE216273
Discount Schedule	0PE2
GTIN	785901181293
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.0 in (109.2 cm)
Package 1 Width	21.8 in (55.4 cm)
Package 1 Length	17.7 in (45 cm)
Package 1 Weight	302.0005 lb(US) (136.985 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------