

Product data sheet

Specifications



Transformer, drive isolation, dry, 330kVA, 3 phase, 460V delta primary, 460Y/265V secondary, 25D, 150C rise

330T145HDIT

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Drive Isolation Transformer
Enclosure Code	25D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	3 phase
Primary Voltage	460 V delta
Power Rating	330 kVA
Secondary Voltage	460Y/265 V
Full Capacity Taps	2 5 % 1+ 1-
Temperature Rise	150 °C
Winding Material	Aluminium

Ordering and shipping details

Category	US10PE216266
Discount Schedule	0PE2
GTIN	785901300649
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	50.750 in (128.905 cm)
Package 1 Width	42.00 in (106.68 cm)
Package 1 Length	33.00 in (83.82 cm)
Package weight(Lbs)	1580.281 lb(US) (716.803 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No