

4X1.5S1FSS

Transformer, dry type, encapsulated, 1.5kVA,
1 phase, 240x480V primary, 120/240V
secondary, 51X, 115C rise



Main

Product or Component Type	Dry Sealed Transformer
Primary to Secondary Voltage	240 x 480 V 120/240 V
Full Capacity Taps	0

Complementary

Enclosure Code	51X
Phase	1 phase
Power Rating	1.5 kVA
Temperature rise	115 °C
Height	9.5 in (241.30 mm)
Width	10 in (254.00 mm)
Depth	7.75 in (196.85 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Stainless Steel

Environment

Enclosure Type	NEMA 4X
Insulation temperature	356 °F (180 °C)
Product Certifications	CSA CULus UL Listed

Ordering and shipping details

Category	16277-RESIN LVGP XFMR
Discount Schedule	PE2
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------