

# Product data sheet

Specifications



Starter, Definite Purpose, nonreversing, 30A, 2 pole, 1 phase, 110/120VAC 50/60Hz coil, melting alloy overload, NEMA 1

8911DPSG32V02

Product availability: Non-Stock - Not normally stocked in distribution facility

## Main

|                         |                                                  |
|-------------------------|--------------------------------------------------|
| Product                 | Definite Purpose Starter                         |
| Ampere Rating           | 30 A                                             |
| Horsepower Rating       | 2 hp 115 V AC, 1 phase<br>5 hp 230 V AC, 1 phase |
| Maximum Voltage Rating  | 600 V AC                                         |
| Control Circuit Voltage | 110 V AC 50 Hz<br>120 V AC 60 Hz                 |
| Phase                   | 1 phase                                          |

## Complementary

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Enclosure Material      | Painted sheet steel                                |
| Enclosure Rating        | NEMA 1                                             |
| Locked Rotor Amperes    | 180 A 230 V AC<br>150 A 460 V AC<br>120 A 575 V AC |
| Number of Poles         | 2P                                                 |
| Range                   | DPS                                                |
| Overload Type           | Melting alloy                                      |
| Number of Thermal Units | 1                                                  |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CP121381 |
| Discount Schedule | 0CP1         |
| GTIN              | 785901002826 |
| Returnability     | No           |
| Country of origin | US           |

## Packing Units

|                        |                       |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE                   |
| Nbr. of units in pkg.  | 1                     |
| Package 1 Height       | 6.300 in (16.002 cm)  |
| Package 1 Width        | 7.000 in (17.780 cm)  |
| Package 1 Length       | 11.400 in (28.956 cm) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                     |                         |
|---------------------|-------------------------|
| Package weight(Lbs) | 5.600 lb(US) (2.540 kg) |
|---------------------|-------------------------|

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances               |                                        |
|----------------------------------------|----------------------------------------|
| Packaging made with recycled cardboard | Yes                                    |
| Packaging without single use plastic   | Yes                                    |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a> |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |    |
|--------------------------|----|
| Take-back                | No |