



Main

Range	Linergy
Product name	Linergy FH
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	1P
Number of ways	12 ways, type : 1 L with 18 mm pitch
Distance between way	18 mm
Poles distribution	L
Connector type	Tooth
Length in 18 mm modules	12

Complementary

Device presentation	Cuttable
[In] rated current	100 A (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
9 mm pitches	24
Width	220 mm
Colour	Anthracite grey (RAL 7016)
Range compatibility	Multi 9 C60N Multi 9 C60L Multi 9 C60H Multi 9 C60CTRL Acti 9

Environment

Standards	IEC 61439-2
-----------	-------------

Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
-----------------	---

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------