

Product data sheet

Specifications



Wall flange, I-Line Busway, 2000A, 600VAC, 3 phase, 4 wire, vertical [TAA]

ACF13WF

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Wall flange
Range	I-Line

Complementary

Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	17.2 in (436.9 mm)
Width	10.26 in (260.60 mm)
For Use with	Busbar trunking 2000 A aluminium Busbar trunking 2500 A copper

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	US10PE820199
Discount Schedule	0PE8
GTIN	785901812647
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	10.276 in (26.100 cm)
Package 1 Width	0.394 in (1.000 cm)
Package 1 Length	17.205 in (43.700 cm)
Package weight(Lbs)	26.037 lb(US) (11.810 kg)

Compliance

Compliance	TAA Compliant BAA Compliant via COTS
------------	---

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No