Product data sheet
Characteristics

AP50210
BUSWAY PLUG-IN STRAIGHT LENGTH 10FT 225A

Main

Product or component type	Straight length
Range of product	I-Line

Complementary

Line Rated Current	225 A
Short Circuit Rating	22 kA
Busbar Material	Aluminium busbar
Integral Ground	Without protection
Rated Voltage	600 V AC
Number of Phases	3 phase
Wiring configuration	4-wire
Length	10 ft (3.05 m)

Ordering and shipping details

Category	20058-AP 225A 4WIRE-INDL
Discount Schedule	PE8
GTIN	00785901533177
Package weight(Lbs)	68.00 lb(US) (30.844 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months