Product data sheet
Characteristics

AP504GLFI
Busway, I-Line, plug in, elbow, front inside, 400A, 600 VAC, 3 phase, 4 wire, 18 inch by 18 inch, aluminum busbar

Main

Product or Component Type	Elbow
Range	I-Line

Complementary

Rated Current	400 A
Busbar Material	Aluminium busbar
Integral Ground	50 percent capacity integral ground bus
Rated Operational Voltage	600 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Position	Front inside
Orientation	Horizontal
Length	18 in (457.20 mm)
Width	18 in (457.20 mm)

Ordering and shipping details

Category	20067-AP W/GRD 400A 4WIRE-COMM
Discount Schedule	PE8
GTIN	785901436997
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	34.00 lb(US) (15.422 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months