

Product data sheet

Specifications



Safety switch, double throw, non fusible, 200A, 480 VAC/250 VDC, 3 poles, 15 hp, NEMA 1

C82344

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	CSA
Enclosure Rating	NEMA 1 galvannealed steel
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	3
Voltage Rating	250 V DC 480 V AC
Wire Size	AWG 6...300 kcmil copper or aluminium

Complementary

Motor power hp	15 hp at 480 V AC 50-60 Hz for 3 phase motors
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.2 in ² (13.30...127 mm ²) (AWG 6...250 kcmil)
Width	23.88 in (606.55 mm)
Height	30.88 in (784.35 mm)
Depth	11.75 in (298.45 mm)

Ordering and shipping details

Category	US10DE100153
Discount Schedule	0DE1
GTIN	785901995647
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	12.2 in (31.0 cm)
Package 1 Width	24.6 in (62.5 cm)
Package 1 Length	32.008 in (81.3 cm)
Package weight(Lbs)	64.99 lb(US) (29.48 kg)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Circularity Profile


No need of specific recycling operations

Take-back

No

Technical Illustration

Dimensions



Technical Illustration

Wiring diagram

