

Product data sheet

Specifications



Safety switch, heavy duty, non fusible, 400A, 600VAC/VDC, 3 poles, 350HP, NEMA 12

CHU365AWK

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Single Throw Safety Switch
Disconnect Type	Non-fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	400 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Standard Motor Power Rating	50 hp at 600 V DC 50 hp at 250 V DC
Max Motor Power Rating	350 hp at 600 V AC 50/60 Hz for 3 phase motors 250 hp at 480 V AC 50/60 Hz for 3 phase motors 125 hp at 240 V AC 50/60 Hz for 3 phase motors
Wire Size	AWG 1/0...750 kcmil copper or aluminium
Tightening torque	550 lbf.in (62.1 N.m) 0.08...0.6 in ² (53.49...380.0 mm ²) (AWG 1/0...750 kcmil) 550 lbf.in (62.1 N.m) 0.08...0.2 in ² (53.49...152.0 mm ²) (AWG 1/0...300 kcmil)
Height	46.25 in (1174.75 mm)
Width	26.25 in (666.75 mm)
Depth	10.13 in (257.30 mm)

Environment

Certifications	cUL
Enclosure Rating	NEMA 12 galvanized steel

Ordering and shipping details

Category	US10DE100153
Discount Schedule	0DE1
GTIN	785901344629
Returnability	Yes
Country of origin	MX

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	26.700 in (67.818 cm)
Package 1 Width	12.800 in (32.512 cm)
Package 1 Length	50.600 in (128.524 cm)
Package weight(Lbs)	152.00004 lb(US) (68.946 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	2
Package 2 Height	40.000 in (101.600 cm)
Package 2 Width	36.000 in (91.440 cm)
Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	304.00007 lb(US) (137.892 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 232 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	347 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	172 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	547 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	165 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	D0bd462c-e622-40b4-9939-dbd8b5850181
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	90
Circularity Profile	No need of specific recycling operations
Take-back	No