

Product data sheet

Specifications



Enclosed molded case switch, QO Canadian, 60A, 2 pole, 240VAC, 22kA, air conditioning, NEMA 3R, cUL

CQO200TR

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Enclosed molded case switch
Range of Product	QO

Complementary

Current Rating	60 A
Number of Phases	1 phase
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker QO 2P
Product Certifications	CSA
Voltage Rating	240 V AC
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Tightening Torque	Cover 20 lb.in
Height	9.3 in (236 mm)
Width	4.8 in (122 mm)
Depth	3.7 in (95 mm)

Ordering and shipping details

Category	US1DE3A00156
Discount Schedule	DE3A
GTIN	785901652069
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.00 in (17.78 cm)
Package 1 Width	9.30 in (23.62 cm)
Package 1 Length	20.0 in (50.8 cm)
Package weight(Lbs)	3.0005 lb(US) (1.361 kg)
Unit Type of Package 2	CAR

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 2	10
Package 2 Height	7.00 in (17.78 cm)
Package 2 Width	9.30 in (23.62 cm)
Package 2 Length	20.0 in (50.8 cm)
Package 2 Weight	30.69 lb(US) (13.92 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	400
Package 3 Height	7.00 in (17.78 cm)
Package 3 Width	9.30 in (23.62 cm)
Package 3 Length	20.0 in (50.8 cm)
Package 3 Weight	1227.5 lb(US) (556.8 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	11 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	10 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	88
Circularity Profile	No need of specific recycling operations
Take-back	No