

EE15S60H

Transformer, dry type, DOE 2016, 15kVA, 1 phase, 208V primary, 120/240V secondary, 17D, 150C rise



Main

Product	Energy Efficient Transformer
Enclosure Code	17D
Enclosure Type	NEMA 2
Insulation Temperature	428.0000000000 °F (220 °C)
Phase	1 phase
Primary Voltage	208 V
Power Rating	15 kVA
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Temperature Rise	150 °C
Winding Material	Aluminium

Ordering and shipping details

Category	US1PE2E16284
Discount Schedule	PE2E
GTIN	785901840763
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	220.00 lb(US) (99.79 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------