

Product data sheet

Characteristics

EE250S3H

Transformer, dry type, DOE 2016, 250kVA,
1 phase, 240x480V primary, 120/240V
secondary, 25D, 150C rise



Main

Product	Energy Efficient Transformer
Enclosure Code	25D
Enclosure Type	NEMA 2
Insulation Temperature	428.0000000000 °F (220 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	250 kVA
Secondary Voltage	120/240 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	150 °C
Winding Material	Aluminium

Ordering and shipping details

Category	US1PE2E16284
Discount Schedule	PE2E
GTIN	785901490531
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	494.88 in (1257 cm)
Package 1 Width	379.92 in (965 cm)
Package 1 Length	300.0000000000 in (762 cm)
Package 1 Weight	3400.00 lb(US) (1542.214 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------