

Product data sheet

Specifications



Transformer, dry type, DOE 2016, 150kVA, 3 phase, 480V delta primary, 208Y/120V secondary, 22M, 80C rise, Cu

EXN150T3HBCU

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Square D
Product or Component Type	Transformer
Device short name	DOE 2016
Transformer type	Energy efficient
Device Application	Low voltage electrical distribution

Complementary

Box number	22M
Phase	3 phase
Rated operational power in VA	150 kVA
Network Frequency	60 Hz
Type of cooling	Natural convection
Primary Voltage	480 V delta
Number of tap-offs	2 2.5 % FCAN 4 2.5 % FCBN
Primary operational current	180.42 A 416.36 A 150 kVA
Secondary voltage	208Y/120 V
Coil Material	Copper
Basic IMP level (BIL)	10 kV
Temperature Rise	80 °C 220 °C insulated
DOE Efficiency	99.09 % at 35 % load factor , 167 °F (75.0 °C)
Sound Level	44 dB 7 dB
%IZ	5.45 %
%IX	5.28 %
X/R Ratio	3.91
Inrush current	1332 A
Let Through Current	7.64 kA
Transformer Losses	228 no load (core loss) 2221 load loss (coil loss)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Transformer BTU/HR	1193 16.6 % 1456 25 % 2877 50 % 5246 75 % 8561 100 %
Height	40.6 in (1031 mm)
Depth	32.6 in (827 mm)
Width	33.7 in (855 mm)
Product Weight	1424.01 lb(US) (645.92 kg)
Mounting support	Floor Floor, with 7400FMB Ceiling, with 7400CMB22M
Degree of protection	UL type 2 UL type 3R, with 7400WS22M
Electrical connection	6 Hole Nema Pad secondary 0.4 in (11.1 mm) 8 Hole Nema Pad sec - XO 0.4 in (11.1 mm) 2 Hole Nema Pad primary 0.4 in (11.1 mm)
Number of mounting holes	4 Ø: 0.5 in (13 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

Ordering and shipping details

Category	US1PE2X16256
Discount Schedule	PE2X
GTIN	785901454694
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	40.6 in (103.1 cm)
Package 1 Width	33.7 in (85.5 cm)
Package 1 Length	32.6 in (82.7 cm)
Package weight(Lbs)	1545.0008 lb(US) (700.8 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	33 733 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 052 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	122 kg CO2 eq.
Carbon footprint of the installation phase [A5]	32 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	28 975 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 552 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again




Repack and remanufacture

Recyclability potential, in %	95
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions



Technical Illustration

Wiring diagram

