Product data sheet

Specifications

Main circuit breaker busway tap left, EZ Meter-Pak, 1200A, 240VAC max, 3ph/4W, 1200A bus, 65kA, neut front, Type 1

EZM31200GBNFBTL

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	EZ meter-pak
Product or Component Type	Meter center main unit
Main type	Main Circuit Breaker
Included Items	Circuit-breaker 1) 3P 1200 A 65 kA Closing plate

Complementary

Main rated current	1200 A
Bus rated current	1200 A
Enclosure Material	Painted steel
[Ue] rated operational voltage	208Y/120 V AC 240/120 V delta AC 240/120 V delta
Device mounting	Surface
Number of Phases	3 phase in 3 phase out
Electrical connection	Lugsneutral front Busway left side
Wiring configuration	4-wire
Type of Installation	Indoor
Height	50.48 in (1282.19 mm)
Width	22.36 in (567.94 mm)
Depth	13.63 in (346.20 mm)

Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 1

Ordering and shipping details

Category	US10DE400020
Discount Schedule	0DE4
GTIN	785901984665
Returnability	No
Country of origin	MX

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	50.5 in (128.2 cm)
Package 1 Width	22.4 in (56.8 cm)
Package 1 Length	13.6 in (34.6 cm)
Package weight(Lbs)	285.999 lb(US) (129.727 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Environmental footprint

Total lifecycle Carbon footprint	**3 177 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 256 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**24 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**9 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 698 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**190 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**