

Product data sheet

Specifications



Main circuit breaker busway center tap, EZ Meter-Pak, 1200A, 240VAC max, 3ph/4W, 3000A bus, 65kA, Type 3R

EZM31200GCBA30

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	EZ meter-pak
Product or Component Type	Meter centre busway centre tap main unit
Main type	Main Circuit Breaker
Included Items	Circuit-breaker 1) 3P 1200 A 65 kA main supply, ready assembled Closing plate

Complementary

Main rated current	1200 A
Bus rated current	3000 A
Enclosure Material	Painted steel
[Ue] rated operational voltage	208Y/120 V AC 240/120 V delta AC
Device mounting	Surface
Number of Phases	3 phase in 3 phase out
Electrical connection	Busway
Wiring configuration	4-wire
Height	43.07 in (1093.98 mm)
Width	22.72 in (577.09 mm)
Depth	14.76 in (374.90 mm)

Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	US10DE400020
Discount Schedule	0DE4
GTIN	3606486147917
Returnability	No
Country of origin	MX

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	43.07 in (109.4 cm)
Package 1 Width	22.7 in (57.7 cm)
Package 1 Length	14.8 in (37.5 cm)
Package weight(Lbs)	595.200 lb(US) (269.978 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	4 786 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 615 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	49 kg CO2 eq.
Carbon footprint of the installation phase [A5]	20 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 708 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	395 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.