Product data sheet

Specifications

Main circuit breaker unit, EZ Meter-Pak, 1200A, 240VAC max, 3ph/4W, 1200A bus, 100kA, OH, Type 3R, ERMS

EZM31200JCBTMS

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	EZ meter-pak
Product or Component Type	Meter center main unit
Main type	Main Circuit Breaker
Included Items	Circuit-breaker 1) 3P 1200 A 100 kA main supply, ready assembled Closing plate

Complementary

Main rated current	1200 A
Bus rated current	1200 A
Enclosure Material	Painted steel
[Ue] rated operational voltage	208Y/120 V AC 240/120 V delta AC
Device mounting	Surface
Number of Phases	3 phase in 3 phase out
Service feed location	OH
Electrical connection	Lugs 4 3/0 AWG...500 kcmil copper or aluminium) Lugs 1 6 AWG...300 kcmilground
Wiring configuration	4-wire
Type of Installation	Indoor/outdoor
Height	46.93 in (1192.02 mm)
Width	23.69 in (601.73 mm)
Depth	13.63 in (346.20 mm)

Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	US10DE400020
Discount Schedule	0DE4
GTIN	785901083184
Returnability	No

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	46.9 in (119.2 cm)
Package 1 Width	23.7 in (60.2 cm)
Package 1 Length	13.6 in (34.6 cm)
Package weight(Lbs)	342.001 lb(US) (155.129 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Environmental footprint

Total lifecycle Carbon footprint	**3 469 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 502 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**28 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**11 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 700 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**227 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**