

Product data sheet

Specifications



Main lugs unit, EZ Meter-Pak,
600A, 240VAC max, 3ph/4W,
800A bus, OH/UG, Type 3R, Cu
bus

EZM3600TBCU

Product availability: Stock - Normally stocked in distribution facility

Main

Device short name	EZ
Main Type	Main Lugs
Product or Component Type	Lug
Range of Product	Meter-Pak

Complementary

Wire Gauge	AWG 1/0...750 kcmil 2
Bus rated current	600 A
Device mounting	Surface
Electrical connection	Lugs, line side
Enclosure Material	Steel
Material	Copper: busbar
Product Certifications	UL Listed
Height	17.15 in (435.61 mm)
Width	30.46 in (773.68 mm)
Depth	7.09 in (180.09 mm)

Environment

Enclosure Rating	NEMA 3R
------------------	---------

Ordering and shipping details

Category	US10DE400020
Discount Schedule	0DE4
GTIN	785901476092
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.500 in (19.050 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	20.800 in (52.832 cm)
Package 1 Length	31.300 in (79.502 cm)
Package weight(Lbs)	64.501 lb(US) (29.257 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	40.000 in (101.600 cm)
Package 2 Width	40.000 in (101.600 cm)
Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	645.0004 lb(US) (292.567 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	2 025 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	283 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 692 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	43 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	No

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	95
Circularity Profile	No need of specific recycling operations
Take-back	No