

Product data sheet

Specifications



Safety switch, heavy duty, fusible, 30A, 600VAC, 600VDC, 3 poles, 20hp, NEMA 4, 4X, 5, 304 steel, Crouse-Hinds

H361DSWC

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Receptacle Switch
For Use With	Plug APJ3485 Crouse-Hinds Arktite
Disconnect Type	Fusible disconnect switch
Number of Poles	3
Current rating	30 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 4X/5 stainless steel 304
Maximum Horse Power Rating	5 hp at 480 V AC 50-60 Hz for 3 phase motors 15 hp at 480 V AC 50-60 Hz for 3 phase motors 7.5 hp at 600 V AC 50-60 Hz for 3 phase motors 20 hp at 600 V AC 50-60 Hz for 3 phase motors 5 hp at 250 V DC

Complementary

Short-circuit Current Rating	10 kA H or K 200 kA R or J
Fuse Type	H or K R or J
Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	4-wire
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 lbf.in (5.08 N.m) (AWG 6) 40 lbf.in (4.5 N.m) (AWG 8) 35 lbf.in (4.0 N.m) (AWG 14...AWG 10)
Depth	5.11 in (129.79 mm)
Width	10.79 in (274.07 mm)
Height	16.87 in (428.50 mm)

Environment

Certifications	UL Listed
----------------	-----------

Ordering and shipping details

Category	US10DE100118
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	0DE1
GTIN	785901369356
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	31.437 in (79.849 cm)
Package 1 Width	7.375 in (18.732 cm)
Package 1 Length	13.437 in (34.129 cm)
Package weight(Lbs)	23.0008 lb(US) (10.433 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	88 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	57 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	24 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	89
Take-back	No