Product data sheet

Specifications

Safety switch, heavy duty, non fusible, 60A, 600VAC/DC, 3 poles, 60HP, NEMA 1, Appleton Powertite receptacle

HU362WA

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Receptacle Switch
For Use With	Plug ACP6034BC Appleton Powertite
Disconnect Type	Non-fusible disconnect switch
Number of Poles	3
Current rating	60 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 1
Maximum Horse Power Rating	50 hp at 480 V AC 50-60 Hz for 3 phase motors 60 hp at 600 V AC 50-60 Hz for 3 phase motors 10 hp at 250 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	4-wire
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 lbf.in (5.08 N.m) (AWG 6...AWG 4) 40 lbf.in (4.5 N.m) (AWG 8) 35 lbf.in (4.0 N.m) (AWG 14...AWG 10)
Depth	6.81 in (172.97 mm)
Width	10.5 in (266.7 mm)
Height	18.9 in (480.06 mm)

Environment

Certifications	UL Listed

Ordering and shipping details

Category	US10DE100124
Discount Schedule	0DE1
GTIN	785901775256
Returnability	Yes
Country of origin	US

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	22.50 in (57.15 cm)
Package 1 Width	7.00 in (17.78 cm)
Package 1 Length	10.375 in (26.352 cm)
Package weight(Lbs)	17.000 lb(US) (7.711 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Environmental footprint

Total lifecycle Carbon footprint	**76 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**42 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.8 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**13 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**18 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**Fcbb2f4b-148e-498d-b15c-530db69350d4**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**89**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**