



Main

Product or Component Type	Fuse-switch
Range of Product	QMB Square D

Complementary

Line Rated Current	30 A
Material	Steel
Number of poles	3
Rated Voltage	600 V AC
Device mounting	Surface
Product destination	Distribution board Meter board
Protection Type	Fuse protection
Short-circuit protection	200000 A AIR
Switch Function	TPST
Wiring configuration	Without neutral
Standards	NEMA KS1
Height	6 in (152.4 mm)

Environment

Product Certifications	UL Listed
------------------------	-----------

Ordering and shipping details

Category	US1PE1A00037
Discount Schedule	PE1A
GTIN	785901185970
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	22.379 lb(US) (10.151 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------