

Product data sheet

Specifications



Mini circuit breaker accessory,
QO, lug kit, 125A, 2 pole, 2
spaces, subfeed

QO2125SL

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Lug kit
Marketing Trade Name	QO
Rated Current	125 A
Number of Spaces	2
Number of Phases	2 phases
Voltage Rating	240 V AC

Complementary

Number of Poles	2
Wire Size	AWG 12...AWG 2/0 copper or aluminium
Product Certifications	CSA cURus
Mounting Mode	Plug-in
Height	3.500 in (88.900 mm)
Width	1.494 in (37.948 mm)
Depth	2.310 in (58.674 mm)

Environment

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
---------------------------------------	---------------------------------

Ordering and shipping details

Category	US1DE2A00080
Discount Schedule	DE2A
GTIN	785901031154
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.400 in (8.636 cm)
Package 1 Width	3.800 in (9.652 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	1.600 in (4.064 cm)
Package weight(Lbs)	9.600 oz (272.155 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	51
Package 2 Height	4.000 in (10.160 cm)
Package 2 Width	14.300 in (36.322 cm)
Package 2 Length	21.400 in (54.356 cm)
Package 2 Weight	31.120 lb(US) (14.116 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	19 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	17 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free product

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative

