

Product data sheet

Specifications



Circuit breaker enclosure, QO, 3 phase, 3 spaces, 100A, NEMA1, flush cover, UL

QO3100BNF

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Enclosure
Range of Product	QO

Complementary

Current Rating	100 A
Interrupt Rating	22 kA
Number of Spaces	3
Number of Phases	3 phase
Enclosure Rating	NEMA 1 indoor
Breaker Compatibility	Circuit breaker QO 3P
Product Certifications	UL Listed
Wiring Configuration	3-wire
Electrical Connection	Lugs
Wire Size	AWG 14...AWG 1 copper AWG 12...AWG 1 aluminium
Surface Finish	Baked enamel Gray
Busbar Material	Tin plated copper: busbar
Tightening Torque	35 lb.in, AWG 14...AWG 10, copper 35 lb.in, AWG 12...AWG 10, aluminium Main lugs 40 lb.in, AWG 8...AWG 4, aluminium/copper Main lugs 50 lb.in, AWG 3...AWG 2, aluminium/copper Main lugs 35 lb.in, AWG 14...AWG 10, copper Main lugs 35 lb.in, AWG 12...AWG 10, aluminium
Box Number	13
Cover Type	Flush cover
Ground Bar	Grounding bar (ordered separately)
Enclosure Material	Welded sheet steel
Enclosure Type	Enclosure
Height	13.1 in (333 mm)
Width	5.9 in (149 mm)
Depth	3.4 in (86.4 mm)

Ordering and shipping details

Category	US10DE200023
Discount Schedule	0DE2

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	785901051756
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.6 in (11.7 cm)
Package 1 Width	7.5 in (19.1 cm)
Package 1 Length	15.2 in (38.6 cm)
Package weight(Lbs)	5.7 lb(US) (2.6 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	12 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	11 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again




Repack and remanufacture

Recyclability potential, in %	90
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration


Dimensions



All dimensions are approximate. Also see technical documentation.

Technical Illustration

Wiring diagram



QO3100BNF
QO3100BNS
QO3100BNRB