Product data sheet

Specifications

Switchboard, Speed-D, 400A, 3 phase, 4 wire, 240/120V, 65kA, thermal magnetic, no interior, outdoor

SB324WR

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product Type	Switchboard

Complementary

Number of Phases	3 phase
Wiring Mode	4 wires
Service Voltage	208Y/120 V 240/120 V
Mains Ratings	400 A
Main Breaker Trip Unit	Thermal-magnetic
SCCR	65 kA 240 V AC
Height	90 in (2286 mm)
Width	36 in (914.4 mm)
Depth	24.5 in (622.3 mm)

Environmental

Enclosure Rating	NEMA 3R outdoor)

Ordering and shipping details

Category	US1PE1A09441
Discount Schedule	PE1A
GTIN	785901188735
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package weight(Lbs)	620.000 lb(US) (281.227 kg)

Contractual warranty

Warranty	18 months

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Take-back	**No**