Product data sheet
Characteristics

SSP04XDSE20A
Surge protection device, XDSE, 200kA, 480Y/277 V, 3 phase, 4 wire, SPD type 2

Main

Product	Surge protection device

Complementary

Voltage Rating	480Y/277 V AC
MCOV	320 V
Surge Current	200 A per phase
Voltage Protection Rating	1200 V L-N 1200 V L - G 1200 V L - L 2000 V N - G
Rated Current	20 kA
Number of Phases	3 phase
Wiring Configuration	4-wire
Height	6.0 in (152 mm)
Width	6.0 in (152 mm)
Depth	4.0 in (101 mm)

Environment

Enclosure Rating	NEMA 4X

Ordering and shipping details

Category	US1DE1B08466
Discount Schedule	DE1B
GTIN	785901085096
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 in (15.2 cm)
Package 1 Width	6.0 in (15.2 cm)
Package 1 Length	4.0 in (10.1 cm)
Package 1 Weight	3.911 lb(US) (1.774 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes