

SYLVANIA

Edge-Lit Panels



1. 5-year limited product warranty
2. Operating temperature range between -4°F and +104°F (-20°C and +40°C)
3. Suitable for use in dry location only
4. Not intended for use with dimmers, emergency light fixtures or exit lights
5. Lamp dims via wireless control and will not operate with a dimmer switch; remove all existing dimmers and replace with a regular switch; leave lamp in ON position
6. Installation: Junction box is mounted on back of panel with knock outs for input wiring. Lay in recessed ceiling applications on non-insulated standard 15/16" T-grid
7. To prevent product malfunction and/or electrical shock this product must be properly grounded

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.sylvania.com/fcc15b.

**LED Lamp lifetime is defined as the number of hours when 50% of a large group of identical lamps reaches 70% of its initial lumens.

Application

Edge-Lit Panels are offered in three sizes for illuminating offices, retail or hospitality areas.

Benefits and Features

- DLC Premium listing increases rebate opportunities
- Edge-lit technology combined with diffused lens offers even and uniform lighting
- 3500K, 4000K, and 5000K color temperature
- CRI >80
- Suitable for use in closets, compliant with NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5)

Electrical

- 120-277V_{AC}
- LED driver is a constant current device
- Power factor ≥90%
- THD ≤20%

Wattage Comparison

Panel Size	Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
2x2	3x17W T8	48	32	33%
	2xU31W T8	56	32	43%
2x4	3x28W T8	64	40	38%
	3x32W T8	75	40	47%
	4x28W T8	97	40	59%
	4x32W T8	112	40	64%



Ordering Information

Item Number	Panel Size	Wattage	Lumens	Voltage	CCT	CRI	Life
65233	2x2	32	3200	120-277	4000K	80+	50,000
65234	2x2	32	3200	120-277	5000K	80+	50,000
65235	2x4	40	4000	120-277	4000K	80+	50,000
65236	2x4	40	4000	120-277	5000K	80+	50,000

Lamp Dimensions

