

Rigid Bushings

Insulated - 105°C Thermoplastic Liner - Hot Dip Galvanized

Features

- Liner is rated flame retardant to 105°C

Applications

- Indoor or outdoor use
- Use with locknut to terminate Rigid or IMC conduit to an outlet box
- Plastic liner prevents damage to wire insulation

Standard Material


- Malleable iron
- Plastic insulator

Standard Finish

- Hot dip galvanized



Conforms to finish thickness
ASTM A123/123M
UL 514A
Fed. Spec. A-A-50563
CSA C22.2 No. 18.3
NEMA FB-1



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
311MHDG	02332	1/2"	40	400	29	1.08	.57
312MHDG	02333	3/4"	40	400	35	1.31	.57
313MHDG	02334	1"	25	250	31	1.61	.65
314MHDG	02310	1-1/4"	20	200	29	1.91	.71
315MHDG	02311	1-1/2"	10	100	23	2.16	.73
316MHDG	02312	2"	10	100	25	2.72	.73
317MHDG	02313	2-1/2"	5	50	24	3.23	.94
318MHDG	02314	3"		25	13	3.88	.94
319MHDG	02315	3-1/2"		10	7	4.43	.94
320MHDG	02318	4"		10	8	4.89	.94