

Straight Liquidtight Connectors

With Grounding Lug - Malleable Iron

Features

- Liquidtight
- Lay-in grounding lug
- Insulated throat protects conductors from abrasion damage
- Zinc electro plated for excellent durability

Applications

- Use to connect liquidtight conduit and terminate an external bonding conductor that runs parallel to the conduit
- The NEC code specifies length limitations and that the bonding jumper must be parallel to the conduit
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I



Standard Material


- Malleable iron
- Steel locknut
- Aluminum lug

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL 467 - UL 486A
- Fed. Spec: W-S-610E
- NEMA: GR 1-2017



Catalog Number	UPC	Conduit Size	Lug Size	Unit Carton	Ship Case	Weight/Case	Inches	
							A	B
470SGR	86858	3/8"	14-4	10	100	22	1.18	1.72
471SGR	86859	1/2"	14-4	10	100	23	1.36	1.73
472SGR	86860	3/4"	14-4	5	50	18	1.61	1.81
473SGR	83237	1"	14-4	5	50	24	1.89	1.85
474SGR	86862	1-1/4"	14-4	2	20	16	2.39	2.05
475SGR	86863	1-1/2"	14-4	2	20	18	2.62	2.38
476SGR	86864	2"	14-4	2	20	27	3.24	2.49
477SGR	86865	2-1/2"	1/0-14	---	1	7	3.89	3.21
478SGR	86866	3"	1/0-14	---	1	8	4.74	3.37
479SGR	86867	3-1/2"	6/250	---	1	8	5.31	3.40
480SGR	86868	4"	6/250	---	1	10	5.82	3.66