

Flexible Steel Conduit

UL Listed Reel



Features

- Hot dipped galvanized zinc coating
- Corrosion and crush resistant
- Flexibility for simplified positioning
- Smooth interior for easy wire pull-through
- Easy installation to follow contours

Applications

- Voice, data, communications and video cables
- Motor feeder, branch and control circuit conductors and cables
- Remote-control, signaling and power limited circuit conductors and cables; Class 1-3
- Cables of power-limited or non-power limited fire alarm circuits, fire alarm system conductors
- Environmental air-handling spaces
- Elevators, escalators, and hoistways
- Concealed or exposed installations
- Metal raceway for wires and cables
- Grounding conductor for lengths up to 6 feet



Standard Material

- Galvanized steel

Standard Finish

- Hot dip galvanized zinc coating

Catalog Number	UPC	Size	Feet Reel	Ship Case	Weight/ Case	Thickness	Inside Diameter Min.	Inside Diameter Max.	Outside Diameter Min.	Outside Diameter Max.
5200RUL	87305	3/8"	1000'	1000	250	.64	.393	.393	.560	.610
5201RUL	87306	1/2"	1000'	1000	316	.64	.625	.645	.860	.920
5201R500UL	87307	1/2"	500'	500	164	.64	.625	.645	.860	.920
5202RUL	87308	3/4"	1000'	1000	397	.64	.812	.835	1.045	1.105
5202R500UL	87309	3/4"	500'	500	203	.64	.812	.835	1.045	1.105
5203RUL	87310	1"	400'	400	265	.76	1.000	1.040	1.300	1.380
5204RUL	87311	1-1/4"	200'	200	154	.76	1.250	1.300	1.550	1.630
5205RUL	87312	1-1/2"	150'	150	129	.76	1.500	1.575	1.850	1.950
5206RUL	87313	2"	100'	100	107	.76	2.000	2.080	2.350	2.454