

FS and FD Cast Device Single Gang Boxes

FSC and FDC Type - Single Hub - Heavy Duty

Hot Dip Galvanized

Features

- Suitable for use in concrete
- Tapered threaded hubs-NPT
- Internal grounding screw
- Suitable for wet locations when used with cover and neoprene gasket (FSFDCG)

Applications

- For use in areas where boxes are exposed to harsh locations
- Provides opening for making splices
- Serves as a pull box for conductors
- Allows connection for branch conduit runs

Standard Material


- Malleable iron

Standard Finish

- Hot dip galvanized



Conforms to finish thickness
ASTM A123/123M
UL 514A
Fed. Spec. A-A-50563
CSA C22.2 No. 18.3
NEMA FB-1



Catalog Number	UPC	Size	Ship Case	Weight/ Case	Inches		
					A	B	C
FS TYPE							
FS1MHDG	01799	1/2"	10	24	6.07	2.93	2.20
FS2MHDG	01800	3/4"	10	25	6.07	2.93	2.20
FS3MHDG	01804	1"	10	25	6.07	2.93	2.20
FD TYPE - DEEP							
FD1MHDG	01805	1/2"	10	28	6.09	2.97	2.90
FD2MHDG	01806	3/4"	10	29	6.09	2.97	2.90
FD3MHDG	01811	1"	10	29	6.09	2.97	2.90