

FS and FD Cast Device Double Gang Boxes

FSC & FDC Type - Dual Hub - Heavy Duty Hot Dip Galvanized

Features

- Suitable for use in concrete
- Tapered threaded hubs-NPT
- Internal grounding screw
- Suitable for wet locations when used with cover and neoprene gasket (FSFDCG)

Applications

- For use in areas where boxes are exposed to harsh locations
- Provides opening for making splices
- Serves as a pull box for conductors
- Allows connection for branch conduit runs

Standard Material


- Malleable iron

Standard Finish

- Hot dip galvanized



Conforms to finish thickness
ASTM A123/123M
UL 514A
Fed. Spec. A-A-50563
CSA C22.2 No. 18.3
NEMA FB-1



Catalog Number	UPC	Size	Ship Case	Weight/ Case	Inches		
					A	B	C
FSC TYPE							
FSC21MHDG	01820	1/2"	10	34	5.32	4.71	2.20
FSC22MHDG	01821	3/4"	10	34	5.32	4.71	2.20
FSC23MHDG	01828	1"	10	37	5.32	4.71	2.20
FDC TYPE - DEEP							
FDC21MHDG	01822	1/2"	10	38	5.31	4.70	2.90
FDC22MHDG	01824	3/4"	10	39	5.31	4.70	2.90
FDC23MHDG	01825	1"	10	40	5.31	4.70	2.90