

Vaporproof Fixtures

Features

- Wall mounting
- Also available in ceiling, or pendant mounting
- All assembled fixtures are equipped with 5 holes and available with 1/2" & 3/4" threaded holes
- Socket with leads
- Heat resistant glass globe
- Prevents moisture entry
- Industrial grade, fully gasketed
- Designed to protect the interior from deteriorating effect of ice, corrosive fumes, and non-explosive vapors
- Gray

Application

- Maintains illumination for safety and performance in inclement weather
- UL listed for wet locations

Standard Material

- Rugged die cast copper free aluminum

Standard Finish

- Premium powder coat finish




VFW100W50CG-1/2"
VFW100W75CG-3/4"




VFICC



VFiGLS



VFW100W50CG-1/2"
VFW100W75CG-3/4"



VFiGLS

VFICC

Catalog Number	UPC	# of Holes	Thread Size	Ship Case	Weight/Case	A	Inches B	C
VFW100W50CG	85237	5	1/2"	6	19	7.25	10	4.13
VFW100W75CG	85238	5	3/4"	6	19	7.25	10	4.13
Vaporproof 7" Glass Globe								
VFiGLS	85155			6	6	3.25	7	3
7" Cast Cage								
VFICC	83936			16	11	4.25	7.25	4.13

UL Listing:

Suitable for wet locations for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-explosive vapors and gases. Approved for maximum 100W incandescent.