




HP RATING	
VOLTAGE	HP RATING
3Φ 250 VAC	10 HP
3Φ 480 VAC	20 HP
3Φ 600 VAC	30 HP

A red cylindrical electronic component, likely a sensor or actuator, with a grey mounting bracket and a multi-pin connector. The component is shown at an angle, highlighting its cylindrical body and the mounting hardware. The red body has some text on it, which is partially obscured but appears to include "THERMISTOR". The grey bracket has a multi-pin connector on one end and a small rectangular feature on the other.

3	REMOVED SINGLE ph RATINGS FROM TABLE & ADDED 3Ø 250VAC PER DCN 220711022022	WHD	7/2022
2	REMOVED HP FROM RATING & ADDED TO HP RATING TABLE BASED ON VOLTAGE, ALL SKUS NOW 600 VAC MAX PER DCN 211210015243	WHD	1/6/22
1	RELEASED PER DCN 200923000832	WHD	10/11/20
REV	DESCRIPTION	APP	DATE

THE DESIGN AND DIMENSIONS OF THE
PRODUCT SHOWN ON THIS DRAWING ARE
SUBJECT TO CHANGE WITHOUT NOTICE.
DIMENSIONS ARE IN INCHES [mm].

TITLE 30A, 3P/4W SWITCHED PIN AND
SLEEVE PLUGS W/ AUXILIARY
CONTACTS



TOLERANCES UNLESS OTHERWISE SPECIFIED .XX = $\pm .01$.XXX = $\pm .005$ ANGLE TOL. $\pm 2^\circ$	DR. BY	WHD	SCALE	1:2
	CHK. BY	DSL	DATE	10/23/20