

H1259CNK -- Liquidtight System



Kellems Grips for UL Type A, non-metallic, flexible, liquidtight conduit are available in straight and 90° male and feature a high quality Hubbell plated steel or malleable iron fitting, complete with a sealing O-ring, lock nut and stainless steel mesh.

Product Specifications

Product Type	Liquidtight System
Liquidtight System Type	Flexible Non-Metallic Liquidtight Conduit Grip Type A
Liquidtight Connector Body Style	90 Degree
Trade Size	1 1/4"
Operating Temperature	-30°F to +225°F (-34°C to +107°C)
Mesh Grip Flammability Rating	UL 94-HB
Fitting Flammability Rating	UL 94-V2
Recommended Knockout Hole Size	1.969 to 2.016 (5.00 - 5.12)
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2.
Mesh Length	9" (22.86)
Dimension E	2.281" (5.79)
Dimension F	.656" (1.67)
Dimension G	2.312" (5.87)
Dimension H	2.344" (5.95)
Dimension I	9.00" (22.86)
Certifications	UL Listed CSA Certified
UPC Number	78358533489
Weight in LBs	1.65
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

