

H2009CNK -- Liquidtight System



Kellems Grips for UL Type A, non-metallic, flexible, liquidtight conduit are available in straight and 90° male and feature a high quality Hubbell plated steel or malleable iron fitting, complete with a sealing O-ring, lock nut and stainless steel mesh.

Product Specifications

Product Type	Liquidtight System
Liquidtight System Type	Flexible Non-Metallic Liquidtight Conduit Grip Type A
Liquidtight Connector Body Style	90 Degree
Trade Size	2"
Operating Temperature	-30°F to +225°F (-34°C to +107°C)
Mesh Grip Flammability Rating	UL 94-HB
Fitting Flammability Rating	UL 94-V2
Recommended Knockout Hole Size	2.453 to 2.500 (6.23 - 6.35)
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2.
Mesh Length	14 1/2" (36.83)
Dimension E	2.937" (7.46)
Dimension F	.656" (1.67)
Dimension G	3.187" (8.09)
Dimension H	2.781" (7.06)
Dimension I	14.50" (36.83)
Certifications	UL Listed CSA Certified
UPC Number	78358533491
Weight in LBs	3.5
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

